

Receiver

From

Society
Reference
Address
Phone
Fax
E-mail

Item n° :

60150950

Model :

EVOPLUS B 40/250.40 M

Pump data

Pressure rating : 1,6 MPa
Min. fluid temperature : -10 °C
Max. fluid temperature : 110 °C
EEI : ≤ 0,22

Minimum suction head :

Temperature °C 90 100
Minimum suction head : m 20 25

Requested data

Flow :
Head :
Fluid (%) :
Fluid Temperature : 20 °C
Density : 998,3 kg/m³
Kinematic viscosity : 1,005 mm²/s
Vapor pressure :



Hydraulic data (duty point)

Flow :
Head :

Materials

Pump body Cast iron 250 UNI ISO 185 - CTF
Impeller Technopolymer
Motor shaft Alumina
Seal ring EPDM
Motor casing Die cast aluminium
Closing flange Stainless steel
Thrust ring support EPDM

Curve tolerance according to ISO 9906



Motor data

Motor brand : DAB
Power input P1 : 0,075 kW
Rated voltage : 1~ 220-240 V 50 Hz
Nominal current : 0,55 A
Degree of protection : IP 44

Dimensions in mm

A	19	D1	100	H2	204
A2	14	D2	110	L	250
B	258	D3	150	L1	125
B1	74	D4	84	L2	125
B2	184	H	176		
D	43	H1	124		

Weight : 7,5 kg

Pump connection

Suction side : DN 40 / PN6, PN10, PN16
Discharge side : DN 40 / PN6, PN10, PN16


Receiver

From

Society
Reference
Address
Phone
Fax
E-mail

EVOPLUS B 40/250.40 M

Curve tolerance according to ISO 9906



Suction side :

DN 40

PN6, PN10, PN16

Discharge side :

DN 40

PN6, PN10, PN16

Flow :

Head :

Rated speed :

2900 1/min

MAIN_PROJECT_TITLE

BUSINESS_PROCESS_IC

OWNER_

ISSUE_DATE

